

# PHYSICAL DATA





Noise Reduction Coeffcient (NRC)

WALL PANELS	SQUARE EDGE	
	25mm	

600 x 600 x 25mm 600 x 1200 x 25mm

600 x 1800 x 25mm


Note: Custom sizes available. Please contact Armstrong representative for custom size options & lead time.



NRC	125	250	500	1000	2000	4000
0.85	0.08	0.38	0.86	1.07	1.04	0.97



ASTM E-84 : Class A





#### FABRIC COLORS SELECTION\*





Sangria

















\*Available upon request

Note: Shade variation among panels may occur for different batches due to the fabric dyeing process.

<sup>\*</sup> Due to printing limitations, shade may vary from actual product

<sup>\* \*</sup>Warranty offered only when installation is carried out as per Armstrong Ceiling Solutions recommendations. For more details please refer the Armstrong Ceilings India website.

# **APPLICATION AREAS**

#### Theatres and Auditoria:

45% wall panel cladding offers excellent noice control in Cinemas and Auditorium



#### Conference room and home theatres:

At least 15-25% coverage is recommended in home theatres and conference rooms. Optra panels with its superior texture can be used to create a sense of warmth along with excellent voice clarity



#### Office and Commercial spaces:

10-15% cladding using Optra wall panels is suitable for general purpose coverage and commercial spaces.

Create patterns on the wall thereby, combining form with functionality



### **CONTACT US**

LA/500/092020

### Knauf Ceiling Solutions (India) Private Limited

Boomerang, A-304, Chandivali Farm Road (near Chandivali Studio) Andheri (E), Mumbai - 400 072. **Contact us: 1860 266 7080** | e-mail : Helpdeskindia@knaufarmstrong.com

